

# NASSIMI

Nassimi LLC T 212.643.8080  
370 Seventh Avenue T 800.521.5208  
Suite 1600 F 212.643.2626  
New York, NY 10001 W www.nassimi.com

## Product Specification Sheet

Pattern: Aura

Date: 06/06/2011

### ENCORE by The Symphony Collection

#### General Specifications

Weight (linear yard)	18.0 oz
Width	54 "
Thickness	0.80 mm
Gauge	N/A
Emboss	Paper
Surface Composition	100% Polyurethane
Substrate Composition	100% Polyester
Substrate Weight	6.5 oz

#### General Treatments

Hydrolysis Resistance	7 yrs	ISO 1419:1995 (Jungle Test)
UV Resistance	200 Hours	CFFA-2 / ASTM G26-96 Method C
Cold Crack	-20 F	CFFA-6 Federal Standard No. 191A-Method 5874
Mildew Resistant	Pass	CFFA-120 / ASTM G21-96
Anti-Bacterial	Pass	CFFA-300 / AATCC* Test Method 147-1998
Anti-Microbial	Pass	CFFA-300 / AATCC* Test Method 147-1998
Cleangene Technology	Yes	
Bleach Resistant	Yes	Diluted 3:1

#### Physical Strength Properties

Abrasion	500,000+ Cycles	CFFA-1A/ Method ASTM D 4157-92
Adhesion	10.3 Warp 10.37 Fill	CFFA 3/ ASTM D751-98
Tear Strength	10.3 Warp 16.2 Fill	CFFA-16/ ASTM D2261-96
Breaking Strength	172 Warp 103 Fill	CFFA-17/ ASTM D751-00
Seam Strength	63.4 Warp 46.3 Fill	CFFA-14/ Method ASTM D751-98
Blocking Resistance	2 Rating	CFFA-4/FTMS 191A-TM5872
Croaking	4.5 Dry 4.5 Wet	AATCC-Method 8-2001

#### Flame Retardancy Standards

California Technical Bulletin 117	Pass	Boston Fire Code (BFD IX-1)	N/A
UFAC Class I	Pass	IMO A.652(16)8.2	Pass
BIFMA CS-191-53, Section 3	Pass	ASTM E84 Adhered: Class I	Pass
BIFMA Upholstery, Section 4	Pass	ASTM E84 Un Adhered: Class I	Pass
NFPA 260	Pass		