

NASSIMI

Nassimi LLC T 212.643.8080
370 Seventh Avenue T 800.521.5208
Suite 1600 F 212.643.2626
New York, NY 10001 W www.nassimi.com

Product Specification Sheet

Pattern: Canyon

Date: 05/26/2011

STUDIO

General Specifications

Weight (linear yard)	28.0 oz
Width	54 "
Thickness	1.00 mm
Gauge	0.040
Emboss	SE737
Surface Composition	PVC
Substrate Composition	Polyester
Substrate Weight	4.0 oz

General Treatments

UV Resistance	1000 Hours	CFFA-2/ ASTM G26-96
Cold Crack	-10 F	CFFA-6 Federal Standard No. 191A-Method 5874
Mildew Resistant	Pass	CFFA-120 / ASTM G21-96
Anti-Bacterial	Pass	CFFA-300 / AATCC* Test Method 147-1998
Anti-Microbial	Pass	CFFA-300 / AATCC* Test Method 147-1998
Resilience SR	Pass	
Bleach Resistant	Pass	Diluted 1:10

Physical Strength Properties

Abrasion	100,000 Cycles	CFFA-1A / Method ASTM D 4157-92
Adhesion	13.0 Warp 12.3 Fill	CFFA-3 / ASTM D751-98
Tear Strength	12.7 Warp 10.4 Fill	CFFA-16 / ASTM D5733-95
Tensile Strength and Elongation	79.4/54.4 Warp 56.0/166.4 Fill	CFFA-17 / ASTM D751-98
Seam Strength	40.0 Warp 29.9 Fill	CFFA-14 / Method ASTM D751-98
Flex Resistance of Finish	25,000 Warp 25,000 Fill	CFFA-10/ ASTM D2097-03(2005)

Flame Retardancy Standards

California Technical Bulletin 117, Section E	Pass	NFPA 260	Pass
UFAC Class I	Pass	Boston Fire Code (BFD IX-1)	N/A
BIFMA CS-191-53, Section 3	Pass	IMO A.652(16)8.2	Pass
BIFMA Upholstery, Section 4	Pass	IMO A.652(16)8.3	Pass
MVSS 302	Pass		