

# NASSIMI

Nassimi LLC T 212.643.8080  
370 Seventh Avenue T 800.521.5208  
Suite 1600 F 212.643.2626  
New York, NY 10001 W www.nassimi.com

## Product Specification Sheet

Pattern: Piano

Date: 07/05/2011

### ENCORE by The Symphony Collection

#### General Specifications

Weight (linear yard)	25.0 oz
Width	54 "
Thickness	0.90 mm
Gauge	36.000
Emboss	Smooth
Surface Composition	100% Polyurethane
Substrate Composition	100% Polyester
Substrate Weight	6.5 oz

#### General Treatments

Hydrolysis Resistance	7 yrs	ISO 1419:1995 (Jungle Test)
UV Resistance	200 Hours	CFFA-2/ ASTM G26-96 Method C
Cold Crack	-20 F	CFFA-6 Federal Standard No. 191A-Method 5874
Bleach Resistant	Yes	Diluted 1:10

#### Physical Strength Properties

Abrasion	500,000 Cycles		CFFA-1A/ Method ASTM D 4157-92
Adhesion	7.5 Warp	6.9 Fill	CFFA-16/ ASTM D5733-95
Tear Strength	170 Warp	90 Fill	CFFA-17/ ASTM D751-98
Seam Strength	50.3 Warp	49.4 Fill	CFFA-14/ Method ASTM D751-98
Blocking Resistance	1 Rating		CFFA-4/ FTMS 191A-TM5872
Crocking	5 Dry	5 Wet	AATCC-Method 8-2001
Flex Testing of Finish	25,000 Warp	25,000 Fill	CFFA-10/ASTM D2097-03(2005)

#### Flame Retardancy Standards

California Technical Bulletin 117	Pass	NFPA 206	Pass
UFAC Class I	Pass	Boston Fire Code (BFD IX-1)	N/A
BIFMA CS-191-53, Section 3	Pass	IMO A.652(16)8.2	Pass
BIFMA Upholstery, Section 4	Pass	IMO A.652(16)8.2	Pass
MVSS 302	Pass	ASTM E 84: Class I or A Rating	Pass