

# NASSIMI

Nassimi LLC T 212.643.8080  
370 Seventh Avenue T 800.521.5208  
Suite 1600 F 212.643.2626  
New York, NY 10001 W www.nassimi.com

## Product Specification Sheet

Pattern: Tanglewood

Date: 09/12/2011

### THE SYMPHONY COLLECTION

#### General Specifications

Weight (linear yard)	33.0 oz
Width	54 "
Thickness	1.00 mm
Gauge	0.040
Emboss	Special
Surface Composition	PVC/Rayon
Substrate Composition	Poly/Rayon
Substrate Weight	N/A oz

#### General Treatments

UV Resistance	40 Hours	CFFA-2 / ASTM G26-96 Method C
Cold Crack	-10 F	CFFA-6 Federal Standard No. 191A-Method 5874
Mildew Resistant	N/A	CFFA-120 / ASTM G21-96
Anti-Bacterial	N/A	CFFA-300 / AATCC* Test Method 147-1998
Anti-Microbial	N/A	CFFA-300 / AATCC* Test Method 147-1998
Resilience FSR	Yes	
Bleach Resistant	N/A	

#### Physical Strength Properties

Abrasion	30,000 Cycles		CFFA-1A/ Method ASTM D 4157-92
Adhesion	TBA Warp	TBA Fill	CFFA 3/ ASTM D751-98
Tear Strength	TBA Warp	TBA Fill	CFFA-16/ ASTM D5733-95
Tensile Strength & Elongation	TBA Warp	TBA Fill	CFFA-17/ ASTM D751-98
Seam Strength	TBA Warp	TBA Fill	CFFA-14/ Method ASTM D751-98
Stretch and Set	TBA Warp	TBA Fill	CFFA-15/ SAE Method J-855

#### Flame Retardancy Standards

California Technical Bulletin 117	Pass	NFPA 260	Pass
UFAC Class I	Pass	Boston Fire Code (BFD IX-1)	N/A
BIFMA CS-191-53, Section 3	Pass	IMO A.652(16)8.2	Pass
BIFMA Upholstery, Section 4	Pass	ASTM E 84: Class I or A Rating	N/A
MVSS 302	Pass		